




HAZE METER - TORONHAZE™

The Haze Meter - ToronHaze™ is designed for precise color measurement, haze measurements, and transmittance analysis of plastics, films, glass, LCD panels, touch screens, and other transparent and semi-transparent materials.

With an open measuring area, it accommodates a variety of sample sizes and shapes, allowing for flexible testing both vertically and horizontally. Utilizing incident light, this advanced meter ensures accurate and reliable results.



APPLICATIONS

ToronHaze-720 Haze and Color Meter for plastics, films, glass, and LCD panels

HAZE AND COLOR METER - ToronHaze™ -720

- All-in-one measurement of color, haze, and spectral transmittance.
- Calculates total transmittance for transparent and translucent samples.
- Ideal for plastic, film, glass, LCD panels, and touch screen materials.

ToronHaze-720 Haze and Clarity Meter with clarity and transmittance measurement

HAZE AND CLARITY METER - TORONHAZE™ -720

- Measures clarity along with color, haze, and spectral transmittance.
- Provides total transmittance results for transparent and translucent samples.
- Suitable for plastics, films, glass, LCD panels, and touch screens.

FEATURES

Features of Haze Meter - ToronHaze™

- Various measurement parameters and professional clarity measurement function
- Comprehensive transmission color parameters
- Complies with ASTM and ISO standards
- Different light sources for different measurement standards
- Compensation measurement for more accurate test results
- Haze QC software included as a standard accessory
- Seven-inch Android touch screen for better user experience
- Open sample measurement area, allowing samples to be measured horizontally or vertically
- Abundant measurement fixtures


TECHNICAL SPECIFICATIONS

Specification of Haze Meter

Type	ToronHaze™-700	ToronHaze™-720
Light Source	Haze/Transmittance: CIE-A, CIE-C, CIE-D65 Chromaticity index: A, C, D50, D55, D65, D75, F1, F2, F3, F4, F5, F6, F7, F8, F9, F10, F11, F12, CMF, U30, DLF, NBF, TL83, TL84	
Standards	ASTM D1003/D1044, ISO13468/ISO14782 JIS K 7105, JIS K 7361, JIS K 7136, CIE No.15, ISO 7724/1, ASTM E1164, DIN 5033, Teil7, JIS Z8722, Condition C	
Parameters	Haze (HAZE), Transmittance (T), Spectral transmittance, CIE Lab, LCh, CIE Luv, XYZ, Yxy, Hunter Lab Munsell MI,CMYK, Whiteness WI(ASTM E313-00,ASTM E313-73, CIE,ISO2470/ R457, Hunter, Taube Berger Stensby), Yellow Index YI(ASTM D1925, ASTM E313-00, ASTM E313-73), Tint(ASTM E313-00), Heterochromatic index Milm, APHA, Pt-Co(Index of platinum cobalt), Gardner, Color difference (AE*ab, AE*CH,AE*uv,AE* cmc(2:1), AE*cmc(1:1),AE*94,AE*00)	Haze (HAZE), Transmittance (T), Spectral transmittance, Clarity CIE Lab, LCh, CIE Luv, XYZ, Yxy, Hunter Lab Munsell MI,CMYK, Whiteness WI(ASTM E313-00,ASTM E313-73, CIE,ISO2470/ R457, Hunter, Taube Berger Stensby), Yellow Index YI(ASTM D1925, ASTM E313-00, ASTM E313-73), Tint(ASTM E313-00), Heterochromatic index Milm, APHA, Pt-Co(Index of platinum cobalt), Gardner, Color difference (AE*ab, AE*CH,AE*uv,^E* cmc(2:1), AE*cmc(1:1), AE*94,AE*00)

Spectral Response	CIE The spectrum function $Y/V(\lambda)$	
Wavelength	400-700nm	
Wavelength Interval	10nm	
Geometry	0/d	
Measurement Area Sample Port	16.5mm/21mm	18mm/25.4mm
Measurement Range	0-100%	
Haze Resolution	0.01%	
Haze Repeatability	Haze < 10%, Repeatability ≤ 0.05 ; Haze $\geq 10\%$, Repeatability $\leq 0.1\%$; Transmittance $\leq 0.1\%$	
Sample Size	Thickness $\leq 145\text{mm}$	
Display	7 Inches Touch Screen	
Memory	Mass storage	
Interface	USB-A, USB-B	
Power	220V (with power cable), (110V is also available)	
Working Temperature	5~40°C, Relative humidity 80% or below (at 35°C), no condensation	
Storage Temperature	-20°C~45°C, Relative humidity 80% or below (at 35°C), no condensation	
Dimension L x W x H	598mm x 247mm x 366mm	

Weight	12kg
Standard Accessory	PC management software (Haze QC)
Optional	Measurement Fixture, Haze standard film
Sphere Diameter	154mm



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com

