




MILITARY SAND & DUST CHAMBER

Military Sand and Dust Chamber is engineered to simulate the harsh desert conditions that military, aerospace, automotive, electrochemical, and electronic equipment may face during real-world operation or storage. This chamber exposes products to controlled dry sand-blowing, dust-blowing, and dust-settling environments, allowing manufacturers to evaluate durability, reliability, and long-term performance under extreme particulate stress.





APPLICATIONS

Applications

1. Military & Defense Equipment Testing
2. Aerospace & Avionic Qualification
3. Automotive & Transportation Components
4. Electronics & Mechatronics Dust Ingress Testing
5. Optical & Precision Instrument Reliability Evaluation

6. Abrasion, Wear, and Mechanical Function Testing
7. Research, Laboratory, and Development Applications



Standard Test

- RTCA/DO-160G : contains environmental testing requirements for aerospace industry
- ISO 20653:2013 : Protection of electrical equipment against objects, water, and access
- MIL STD 810G Method 510.5 Para 4.1.4.2 related test standards : test interruption and post-test procedures for both the Blowing Dust (Procedure I) and Blowing Sand (Procedure II) tests

FEATURES

Military Sand & Dust Chamber Features

1. Built with a fully welded SUS304 stainless-steel inner chamber and reinforces 2 mm structural supports, this chamber offers extreme durability with outstanding corrosion resistance, heat stability, and long service life
2. High speed centrifugal fan for realistic desert wind simulation even can generate controlled wind speeds for both dust (0.5-8.9 m/s) and sand (18-29 m/s)
3. The chamber uses a multi-funnel recirculation system that automatically collects falling particles and keeps them dry through built-in heating.
4. Advanced cabinet sealing ensures zero dust leakage during operation, keeping the laboratory environment safe and clean.
5. The multi-layer tempered glass window includes a built-in automatic wiper system, allowing clear visibility of test items at all times — even during heavy dust or sand cycles.
6. A combination of Bayer high-strength PU foam and ultra-fine glass fiber insulation maintains chamber temperature stability up to +66°C.

THEORY & METHOD

Theory/Method

1. Dust Test Method (Blowing Dust)

To evaluate how equipment withstands fine dust intrusion, impaired cooling, electrical malfunction, and mechanical binding when exposed to airborne dust.

- Dust concentration: 3.5–8.8 g/m³, consisting of 97–99% silicon dioxide.
- Particle size: ≤150 μm, median diameter 20 ± 5 μm.

- Air velocity: 0.5–8.9 m/s depending on test category.
- Humidity: $\leq 30\%$ to prevent dust agglomeration.
- Duration: typically 6 hours at room temperature + 6 hours at high temperature (if required).

Dust is dispersed above the specimen and maintained in suspension using airflow sufficient to simulate natural desert conditions without exceeding 0.2 m/s at the specimen during dust-fall procedures.

After exposure, mechanical parts are actuated to check for clogging or binding, and functional performance is evaluated.




Figure 6: Basic arrangement of equipment applicable to Method Lc1

2. Sand Test Method (Blowing Sand)

To assess resistance to abrasion, erosion, coating damage, and particle impact experienced in sandstorms or aircraft rotor wash.

- Sand concentration: defined per operational environment (0.18–2.2 g/m³).

- Particle size: 150–850 μm , with specific weight distribution requirements.
- Air velocity: 18–29 m/s to ensure particles reach terminal impact speed.
- Specimen distance: approx. 3 meters from the injection point.
- Temperature: $\pm 25^\circ\text{C}$ (first cycle) and $\pm 55^\circ\text{C}$ (second cycles)
- Humidity: $\leq 30\%$ to prevent dust agglomeration.
- Duration: at least 1 hour per axis (first cycle at 25°C , second at 55°C).

The equipment is reoriented between cycles to expose all vulnerable surfaces equally to high-velocity sand abrasion.




Figure 7: Example of a dust spraying system applicable to Method Lc2

3. Dust-Fall (Settling Dust) Method

To measure how equipment tolerates long-term dust accumulation that may obstruct cooling, ventilation, or moving parts.

- Dust settlement rate: 6 g/m²/day as a baseline.
- Duration: Typically 3 days unless otherwise specified.
- Application: Evaluates dust build-up effects on cooling systems, seals, enclosures, and thermal performance.

This method does not require high wind velocity; only enough airflow is used to keep dust suspended before it settles.

TECHNICAL SPECIFICATIONS

Military Sand & Dust Chamber Technical Specifications

Model	ToronSDC-Mi	
Chamber Volume	1000 L	
Inner dimension (W x D x H)	1000 × 1000 × 1000 mm	
Section size	Dust blowing (W x H)	1000 × 1000 mm
	Sand blowing (W x H)	1000 × 500 mm
External dimension (W x D x H)	7000 × 3246 × 2500 mm	
Temperature range	Room temperature to + 66°C adjustable	
Wind speed	Dust blowing	0.5 - 8.9 m/s
	Sand blowing	18 - 29 m/s
Relative humidity	Less than or equal to 22% RH	

Collect system	Automatically collect the falling sand particle and continue to circulate in the chamber
-----------------------	--



TORONTECH

Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com



USA | Canada | EU | UAE | GCC | KSA | India | Africa | Latin America | Asia

