



HYDRAULIC UNIVERSAL TESTING MACHINE 3,000 KN - TTM-3000

TTM-3000 Servo - Hydraulic Universal Testing Machine

TTM-3000 is a high capacity universal testing machine designed with a hydraulic unit located in the lower section of the frame.

It is primarily used for tensile, compression, bending, and shear testing of both metallic and non-metallic materials. The machine's operations and data processing comply with global "Metallic Materials Tensile Testing" standards including ASTM E-8, ISO and others. This machine is ideal for applications in metallurgy, construction, light industry, aviation, aerospace, educational institutions, and research centers.

APPLICATIONS

The Torontech TTM-3000 Universal Testing Machine is a foundational instrument for determining the definitive mechanical properties of a wide range of materials. By performing precise tensile, compression, bending, and shear tests in compliance with key global standards like ASTM E-8, it provides the essential data required for material certification, design validation, and fundamental research, ensuring that materials meet their specified performance and safety criteria.

This critical mechanical analysis is indispensable for quality and safety assurance in:

- **Primary Metals & Manufacturing:** For the essential quality control and certification of raw materials such as steel rebar, structural beams, and metal plates, ensuring they meet the required grade, strength, and ductility specifications.
- **Aerospace & Automotive:** To conduct rigorous testing on high-strength alloys, composites, and fasteners, validating their mechanical properties to ensure the safety, reliability, and structural integrity of critical components.
- **Civil Engineering & Construction:** For qualifying the tensile strength of reinforcing steel, bolts, and structural components, providing the necessary verification to comply with building codes and ensure the safety of bridges, buildings, and infrastructure.

- **Materials Research & Academia:** As a cornerstone of materials science, used for the development of new alloys and advanced materials, and for providing the fundamental data needed to characterize material behavior under load.

FEATURES

Mechanical Process Structure

- **Load Frame:** The Load Frame features a cylinder located at the lower section with chain transmission and hydraulic clamping. The tensile test area is located in the upper part of the frame, while compression, bending, and shear test area is below the moving crosshead.
- **Material and Construction:** The test surface and columns are made from cast steel materials. The pillar and screw are made from Cr40, which is quenched and tempered for rigidity.
- **Cylinder:** The cylinder uses a special process, with strong gap seals for a long service life.
- **Hydraulic Pump:** European-made high-pressure hydraulic pump ensures low noise and smooth operation.
- **Hydraulic Source:** The hydraulic source uses steel plate forming with surface plastic spraying processing. The design allows for clean placement of computers and printers, saving space.

Control and Measurement System

- The system integrates advanced control and uses a full-digital electro-hydraulic servo closed-loop control and measurement system. This enables functions like constant velocity stress, strain, test force, displacement, and maintaining control.
- **Safety Features:** The system includes multiple protection layers such as overload, overcurrent, overvoltage, undervoltage, overspeed, and limit protections.

- **Software:** Equipped with dedicated monitoring and control software, it handles statistical processing of test data, automatically detects lower yield points, tensile strength, elastic modulus, elongation, and more. The computer displays force, displacement, strain, and other parameters in real-time, with dynamic test curve displays and multiple output options for test curves and reports.
- **User Management:** Features hierarchical management of user rights with secure login.
- **Data Processing:** Utilizes advanced multi-threading technology for data collection and sensor data processing to prevent control failures.
- **Report Editing:** Powerful report editing capabilities allow customization and output of desired test results. Data can be saved in Word format for easy editing.
- **Database Management:** Automatically saves all test data and curves, supports curve enlargement, comparison, and provides a robust foundation for laboratory networking.

TECHNICAL SPECIFICATIONS

Maximum Test Force	3000kN / 675,000 lb.f
Test Force Measuring Range	60-3000kN (13,500 – 675,000 lb.f)
Accuracy Level	±1%
Piston Maximum Speed Range	50mm/min
Piston Stroke	250mm
Displacement Resolution	0.01mm
Displacement Measuring Accuracy	±1%
Maximum Tensile Test Space	950mm (37.5 inch)
Round Sample Clamping Diameter	φ25-φ100mm (1-4 inch)

Flat Specimen Clamping Thickness	10-90mm (0.4-3.5 inch)
Distance Between Columns	880mm (35 inch)
Mainframe Dimensions (L × W × H)	Approx. (1573 × 1160 × 3850 mm / 62 x 46 x 152 inch)
Power Supply	380V, 50Hz

Standard Configuration

1. Machine load frame 3000kN
2. Electro-hydraulic servo source
3. Electro-hydraulic servo valve (German VOITH)
4. High pressure oil pump
5. Load Cell: 3,000 kN
6. Manual control box
7. High pressure oil pipe
8. Extensometer (50mm Gauge Length and 10mm Deformation)
9. Dedicated data acquisition card
10. Special measurement and control software
11. Computer

12. Printer

13. Test fixtures

- Round jaw	1 set	Φ25-Φ50mm
- Round jaw	1 set	Φ50-Φ80mm
- Round jaw	1 set	Φ80-Φ100mm
- Flat jaw	1 set	10-45mm
- Flat jaw	1 set	45-90mm
- Compression fixture	1 set	Φ280mm

14. Foundation bolt 4 pieces



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com

