



ELECTRODYNAMIC SHAKER VIBRATION TEST SYSTEM

TTEV series of Electrodynamic Shaker Vibration Test System simulate the vibration environment under the laboratory condition, and test the impact strength as well as reliability of various vibration test applications.

APPLICATIONS

- **Automotive Industry** – Simulates road conditions, vibration fatigue, and transport stress on vehicle components.
- **Aerospace and Defense** – Tests aircraft parts, satellites, and military equipment for vibration resistance under extreme conditions.
- **Electronics and Consumer Products** – Validates durability of circuit boards, devices, and assemblies against sinusoidal and random vibrations.
- **Telecommunication Equipment** – Ensures reliability of sensitive fiber optic and electronic systems under mechanical stress.
- **Packaging and Transport Simulation** – Reproduces shipping vibrations to confirm product integrity during transit.
- **Industrial Machinery and Components** – Evaluates vibration tolerance of heavy-duty mechanical systems and structural parts.
- **Research and Development** – Supports new product design validation with simulations of shock, resonance, and fatigue.
- **Quality Assurance and Certification** – Provides compliance testing with MIL-STD, DIN, ISO, ASTM, IEC, ISTA, GB, JIS, and other international standards.



FEATURES

- Rugged suspension system and linear motion guiding, strong carrying capacity, good guiding functions, high stability.
- Load center airbag with high static stiffness and low dynamic stiffness, strong carrying capacity, perfect performance on amplitude variation.
- High efficiency D class power switching, 3-sigma peak current, low power consumption and minimum harmonic distortion.
- Quick self-diagnosis with safety interlock, high safety reliability.
- Airbag shock isolation device for vibration platform without the need of additional foundation, perfect reproduction of vibrational wave and reduction in vibration transmittance.
- Horizontal and vertical expansion platforms for different applications.
- Simple controller operation.

THEORY & METHOD

TTEV series of electromagnetic vibration testing system simulate the vibration environment under the laboratory condition, and test the impact strength as well as reliability of various vibration test applications. In the laboratory, with the aid of vibration testing system, simulations of reproduction of sinusoidal, random, resonant search and dwell, classical shock and road models, etc. can be achieved. It is essential for product quality assurance, new product research and development.

TTEV series of electromagnetic vibration testing system is specially designed to meet the need for long time operation. Vertical and horizontal vibrations can be achieved by the installation of vibration resistant base. The standard platform is equipped with high efficiency airbag shock isolation device, so that the vibration transmitted to the building can be minimized. There is no need for additional foundation in most of the cases.

A complete set of vibration testing system is composed of shaker, power amplifier and vibration measuring control system, in accordance with the relevant national and international standards (such as: MIL-STD, DIN, ISO, ASTM, IEC, ISTA, GB, GJB,

JIS, BS, etc.) to provide technical support for establishing product quality inspection.

TECHNICAL SPECIFICATIONS

Model	EV203	EV206	EV210	EV220	EV232	EV240	EV250	EV260
Frequency Range □ Hz□	1□ 2500	1-3000	1-3000	1-3000	1-3000	2-2500	1-2500	1-2700
Max. Sine Force (lbs□	300(2.94)	600(5.88)	1000(9.8)	2200(21.56)	3200(31.36)	4000(39.2)	5000(49)	6000(58.8)
Max. Displacement □ mmp-p□	40	50.8	50.8	50.8	50.8	50.8	50.8	50.8
Max. Acceleration(g)	100	100	100	100	100	100	100	100
Max. Velocity □ cm/s□	180	200	200	200	200	200	200	200
Max. Load (kg)	120	200	200	300	500	500	800	1000

Model	EV320	EV330	EV340	EV350	EV360	EV420	EV430	EV440	EV450	EV460
Frequency Range □ Hz□	1-3000	1-2700	1-2700	1-2500	1-2500	1-3000	1-2500	1-2500	1-2500	1-2500
Max. Sine Force	2000(19.6)	3000(29.4)	4000(39.2)	5000(49)	6000(58.8)	2000(19.6)	3200/(31.36)	4000(39.2)	5000(49)	6000(58.8)
Max. Displacement □ mmp-p□	76.2	76.2	76.2	76.2	76.2	101.6	101.6	101.6	101.6	101.6
Max. Acceleration(g)	80	85	200	200	200	200	250	250	250	200
Max. Load □ kg□	400	500	500	800	1000	400	500	500	800	1000



Torontech Inc.

251 Consumers Road, Suite 1200
Toronto, Ontario, M2J 4R3, Canada 

Phone: +1 416 368 2721 | Fax: +1 416 981 7652
Email: info@torontech.com

Torontech, LLC

601 Brickell Key Drive, Suite 700
Miami, FL 33131, USA 

Toll-Free: 1-866-383-7919
Email: sales@torontech.com

Torontech ME FZE

Meydan Grandstand, 6th Floor,
Meydan Road, Nad Al Sheba,
Dubai-261440, UAE 

Phone: +971 488 19252
Email: me@torontech.com

